



Pressure Sensitive Films, Adhesives & Kraft Paper

| Description | Construction | Substrate | Adhesive | Liner | Gloss Level | Applications |
|---|---------------------|---|---|---|---|--|
| PSA Overlaminates Film | | | | | | |
| Gloss Optically clear to enhance image color | 3 + 1 | 3.2 mil Calendared PVC 105 GSM | 1 mil Solvent Acrylic pH value 7.0 | 105 gsm White Paper Silicon coated | ASTM D-523 @ 60° 100 | Signage POP displays Posters & Prints |
| Luster Semi-gloss to minimize reflections | 3 + 1 | 3.2 mil Calendared PVC 105 GSM | 1 mil Solvent Acrylic pH value 7.0 | 105 gsm White Paper Silicon coated | ASTM D-523 @ 60° 30 | Window Displays |
| Matte Non-reflective to eliminate light glare | 3 + 1 | 3.2 mil Calendared PVC 105 GSM | 1 mil Solvent Acrylic pH value 7.0 | 105 gsm White Paper Silicon coated | ASTM D-523 @ 60° 15 | Show Graphics POP Displays |
| Textured Matte 3 Mil Crystalline surface minimizes glare | 3 + 1 | 3.2 mil Textured PVC 105 GSM | 1 mil Solvent Acrylic pH value 7.0 | 105 gsm White Paper Silicon coated | ASTM D-523 @ 85° 8 | Show & In-store Graphics |
| Textured Matte 5 Mil Crystalline surface with added rigidity | 5 + 1 | 5 mil Textured PVC 165 GSM | 1 mil Solvent Acrylic pH value 7.0 | 105 gsm White Paper Silicon coated | ASTM D-523 @ 85° 6 | Trade Show Panels |
| Anti-Graffiti Coated surface protects from stains & abrasion | 1.5 + 1 | 1.5 mil hard Coated PET 50 gsm | 1 mil Solvent Acrylic pH value 7.0 | 105 gsm White Paper Silicon coated | ASTM D-523 @ 60° 90 | Protect signs & graphics from vandalism |
| Dry Erase Gloss Polypropylene surface suitable for short term dry erase markers | 2 + 1 | 2 mil polypropylene non-treated | 1 mil Solvent Acrylic pH value 7.0 | 105 gsm White Paper Silicon coated | ASTM D-523 @ 60° 90 | Write/erase planners, maps, displays, reuseable boards |
| PSA Mounting Adhesive | | | | | | |
| Clear Clear Polyester carrier for general use. Superior bond to Sintra & colored boards | 1 + 1 | 1 mil Polyester carrier Clear | 1 mil Solvent Acrylic Permanent adhesive pH value 7.0 | 110 gsm White Paper Silicon coated | N/A | Mounting to plastic surfaces Gatorboard & Masonite, Posters, Digital prints |
| White White Polypropylene carrier for added opacity. Superior bond to Sintra & colored boards | 2 + 1 | 2 mil Polypropylene carrier White | 1 mil Solvent Acrylic Permanent adhesive pH value 7.0 | 110 gsm White Paper Silicon coated | N/A | Mounting to dark substrates Black gatorfoam Indoor Displays |
| Front Optically clear Polyester carrier for mounting images to Plexiglas | 1 + 1 | 1 mil Polyester carrier Optically clear | 1 mil Solvent Acrylic Permanent adhesive pH value 7.0 | Two 1 mil Polyester liners Silicon coated | N/A | Backlit applications |
| Window Clear PET carrier & embossed adhesive liner for face mounting temporary graphics | 1 + 1 | 1 mil Polyester carrier clear | 1 mil Aqueous permanent 0.5 Aqueous re-positionable adhesive pH value 7.0 | 110 gsm White Paper 3 mil Textured LDPE with printed grid pattern | N/A | Face mounting graphics to windows |
| Kraft Paper | | | | | | |
| Brown Double sided machine finished for smoother operation | 30# basis weight | Virgin fibers with a low re-pulped mill scrap content | N/A | N/A | Double sided machine calendared smooth finish | Backing paper used for single-sided lamination Protects roller from adhesive |

P.O. Box 1097 Maryland Heights, MO 63043

sales@gfpartnersllc.com 800-986-2005

www.gfpartnersllc.com