



Gfp

Graphic Finishing
partners

Where Finishing Comes First.

Gfp 563TH-4RS

Production Top Heat Laminator

What's the best way to make your production even better? Shorten film loading time? Make fewer film changes? Increase throughput speed? The 563TH-4RS does all that and more.

MAXIMIZE PRODUCTIVITY

Inline Rotary Slitters

FAST ROLL CHANGES

Front/Rear Swing-out Shafts

EASY LOADING

3" Aluminum Quick-Grip Shafts

RUGGED DESIGN

Metal Alloy Heaters

VERSATILE

Roll-to-Roll Operation



Overlamination • Mounting • Board Pre-coating

Spend less time on set-ups and changeovers with swing-out supply shafts.

50% faster throughput and quick application changes save time, effort and money.



- Swing-out Quick-Grip Supply Shafts
- Drop-in Quick-Grip Rewind Shafts
- Photoelectric Eye for Safety
- Includes Rear Rewind with Rotary Slitters
- Swing-up Feed Table & 38" Output Height
- Metal Alloy Heater Reduces Breakage
- 4.5" Diameter Rollers
- Roller Gap Measurement Scale



Includes motorized rear
rewind with rotary slitters
for roll-to-roll applications



Media alignment disks keep
supply rolls from telescoping

563TH-4RS

Rugged Design
Professional Quality
Proven Performance
Economically Priced

APPLICATIONS

Signs
Banners
POP Displays
Trade Show Displays
Graphic Mounting
Photo Mounting
Dry-erase Boards
Floor Graphics
Window Graphics
Vehicle Graphics

Warranty:

2 year parts & labor.
Installation is available.

<i>Laminating Width</i>	63"
<i>Roller Diameter</i>	4.5"
<i>Roller Gap</i>	1"
<i>Rear Rewind with Slitters</i>	Included
<i>Maximum Temperature</i>	140°F
<i>Laminating Speed</i>	0-20 ft/min
<i>Pressure Adjustment</i>	Hand Wheel
<i>Heat Method</i>	Metal Alloy heater
<i>Max. Roll Diameter</i>	8" OD (top); 16" OD (bottom)
<i>Supply Shafts</i>	2 Swing-out
<i>Swing-out Shaft Maximum Weight</i>	115 lbs.
<i>Tension Adjustment</i>	Single Knob
<i>Power Supply</i>	110v 12A
<i>Power Consumption</i>	1320W
<i>Foot Pedal</i>	Included
<i>Stand with Casters</i>	Included
<i>Dimensions</i>	87" x 26.5" x 52.5"
<i>Net Weight with tand</i>	491 lbs.
<i>Shipping Dimensions (L x W x H)</i>	90" x 33" x 46" 828 lbs.

cTUVus
Safety
Approval



Your local dealer is:



Gfp Graphic Finishing
partners

