

Gfp 300 Series

Professional Top-Heat Laminators

Upgrade to professional top-heat performance. Easy setup. Low maintenance.

The Gfp 300 Series gives sign shops and digital printers an affordable way to handle pressure-sensitive applications with professional-level results. Unlike the 200 Series laminator platform, the 300 Series adds integrated roll-to-roll capability and top heat for better overlamination, mounting, and board pre-coating performance.



Integrated rear rewind for roll-to-roll applications



Media alignment disks prevent media supply roll from telescoping during operation.



Perfect for mounting, overlamination and board pre-coating.

Built for Performance

- Labor-saving Quick Grip film shafts for fast loading
- Swing-up feed table with 38" input height
- Photoelectric eye for operator safety
- Durable metal alloy heater for consistency
- 5" diameter rollers for smooth, professional results

Ideal Applications:

- Signs and Banners
- POP Displays
- Trade Show Graphics
- Photo and Graphic Mounting
- Dry-Erase Boards
- Floor and Window Graphics
- Vehicle Graphics

Key Features

- Top heat for better laminate results
- Rear rewind for roll-to-roll capability
- Quick Grip shafts for easy film loading
- 5" rollers for smooth finishing
- Photoelectric safety eye
- ***Two year warranty includes parts and labor!***





Scan the QR code to watch demo videos for the GFP 300 Series.

- Product walk-throughs: installation, features, internal views
- Applications: roll-to-roll, mounting, pre-coating, cut-sheet, and more

Rugged Design • Professional Quality • Proven Performance • Economically Priced

Item	355TH Specification	363TH Specification
Laminating Width	55"	63"
Roller Diameter	5"	5"
Maximum Speed (ft/min)	20 ft/min	20 ft/min
Main Roller	Rubber	Rubber
Maximum Roller Gap	1"	1"
Roller Gap Adjustment	Hand Wheel	Hand Wheel
Unwinds	Top/Bottom	Top/Bottom
Liner Rewind	Chain Link	Chain Link
Supply Shafts	3" Quick Grip	3" Quick Grip
Tension Adjustment	Single Knob	Single Knob
Maximum Supply Roll Diameter	6" OD	6" OD
Maximum Temperature	140°F	140°F
Heating Element	Metal Alloy Heater	Metal Alloy Heater
Power Requirements	120V 11A	120V 12A
Power Consumption	1300W	1440W
Rear Rewind	Integrated	Integrated
Foot Pedal	Included	Included
Stand With Casters	Included	Included
Machine Dimensions (L x W x H)	72" x 23" x 48"	80" x 23" x 48"
Net Weight With Stand	350 lbs	380 lbs
Shipping Dimensions (L x W x H)	79" x 26" x 30" (472 lbs.)	87" x 26" x 30" (507 lbs.)



cTUVus
Safety Approval

Your Local Dealer:



gfpartnersllc.com | 800.986.2005