

# Gfp Machine Overview

**WIDE FORMAT LAMINATORS**  
**RUGGED DESIGN**  
**PROFESSIONAL QUALITY** **PROVEN**  
**PERFORMANCE**  
**ECONOMICALLY PRICED**



	865DH-4R	663TH	563TH-4RS	363-TH	355-TH	263-C	255-C	230-C
Heat / Cold	Dual Heat	Top Heat Assist	Top Heat Assist	Top Heat Assist		Cold		Cold
Laminating Width	65"	63"	63"	63"	55"	63"	55"	30"
Maximum Speed (feet/minute)	13	20	20	20		13		11.5
Speed Control	Variable	Variable	Variable	Variable		Variable		Variable
Maximum Temperature	266° F	140°F	140°F	140°F		-		-
Heating Method	Quartz Tube	Metal Alloy	Metal Alloy	Metal Alloy		-		-
Mounting Gap	1"	1"	1"	1"		1"		1/2"
Pressure/Gap Adjustment	Infinite	Infinite	Infinite	Infinite		Infinite		Infinite
Pressure/Gap Mechanism	Dual Hand Wheel	Electric	Hand Wheel	Hand Wheel		Hand Wheel		Hand Wheel
Roller Diameter	5"	5"	4.5"	5"		4.5"		2.5"
Main Rollers	Silicone	Silicone	Silicone	Rubber		Rubber		Silicone
Supply Shaft	Swing Out with 3" Quick Grip	Swing Out with 3" Quick Grip	Swing Out with 3" Quick Grip	3" Quick Grip		3" Quick Grip		1" Shaft / Adaptors
Tension Adjustment	Single Knob	Single knob	Single knob	Single knob		Single knob		Dual brakes
Film Tension Sensor	-	✓	-	-		-		-
Digital Microcontroller	-	✓	-	-		-		-
Color Graphic Display	-	✓	-	-		-		-
Touchscreen Interface	-	✓	-	-		-		-
Operating Tutorials	-	✓	-	-		-		-
Roll Label Printer	-	✓	-	-		-		-
Web Clutch	✓	-	-	-		-		-
Motorized Liner & Rewind	✓	✓	✓	Chain Link		Chain Link		✓
Roll to Roll Capable	✓	✓	✓	✓		-		-
Rear Rewind	✓	✓	✓	✓		-		-
Inline Slitting	-	✓	✓	-		-		-
Front Unwind	2	✓	✓	✓		✓		✓
Foot Pedal	✓	✓	✓	✓		✓		✓
Optical Safety Eyes	✓	✓	✓	✓		✓		✓
Stand	✓	✓	✓	✓		✓		✓
Swing Up Feed Table	✓	✓	✓	✓		Fixed		✓
Power Supply	240v 24A	120v 12A	110v 12A	120v 12a	120v 11a	110v 0.4A		110v 0.3A
Power Consumption	5760W	1440W	1320W	1440W	1320W	44W		33W
Warranty Parts	1 year	1 year	1 year	1 year		1 year		1 year
Warranty Labor	1 year	1 year	1 year	1 year		1 year		1 year
Installation & Training	Included	Optional	Optional	Optional		Optional		Optional
Net Weight (LBS.)	846	675	491	376	321	322	257	117
Dimensions	87 x 34 x 49"	83 x 31 x 63"	87 x 26.5 x 52.5"	80 x 23 x 48"	72" x 23" x 48"	80" x 24" x 55"	73 x 24 x 55"	43 x 17 x 42"
Safety Approval	cTUVus	cTUVus	cTUVus	cTUVus	cTUVus	cTUVus	cTUVus	cTUVus