

# Gfp Thermal Film

GFP Thermal Polyester films deliver durable performance with low melt adhesive technology designed for efficient finishing. Available in multiple thicknesses with white opaque and luster finishes, these films activate between **185°–195°F** for reliable bonding at lower temperatures.

All products are supplied on a **3" core** and individually poly-wrapped for protection. Available roll sizes are listed below.

Gloss – 3 mil (Polyester + Adhesive: 1 + 2)			
Part Number	Width (Inches)	Length (Feet)	Square Foot (ft <sup>2</sup> )
LM 3G 38500	38	500	1583
LM 3G 43500	43	500	1792
LM 3G 51500	51	500	2125

Matte – 3 mil (Polyester + Adhesive: 0.5 + 2.5)			
Part Number	Width (Inches)	Length (Feet)	Square Foot (ft <sup>2</sup> )
LM 3M 38500	38	500	1583
LM 3M 51500	51	500	2125

Gloss – 5 mil (Polyester + Adhesive: 2 + 3)			
Part Number	Width (Inches)	Length (Feet)	Square Foot (ft <sup>2</sup> )
LM 5G 38250	38	250	792
LM 5G 43250	43	250	896
LM 5G 51250	51	250	1063

Gloss – 10 mil (Polyester + Adhesive: 4 + 6)			
Part Number	Width (Inches)	Length (Feet)	Square Foot (ft <sup>2</sup> )
LM 10G 38250	38	250	792
LM 10G 51250	51	250	1063

