

Gfp 865DH-4RS

Versatile Dual Heat Laminator

Ultimate flexibility for thermal & cold finishing. One laminator. More jobs. More profit.

The Gfp 865DH-4RS is built for finishing professionals who need versatility, quality, and value in one machine.



Includes motorized rear rewind with rotary slitters for roll-to-roll applications.



Media alignment disks keep supply rolls from telescoping.



Perfect for laminating, mounting, and encapsulating.

Built for Performance

- Produce thermal encapsulation with low-melt films (1.5–10 mil).
- Handles both pressure-sensitive and thermal lamination and mounting.
- Fast, efficient finishing with fewer changeovers
- Swing-Out Quick Grip supply shafts reduce setup time.
- Designed for years of maintenance-free production.

Ideal Applications:

- Signs & Posters
- POP & Trade Show Displays
- Dry-Erase Boards
- Graphic & Photo Mounting
- Floor & Window Graphics
- Vehicle Graphics

Key Features

- Labor-saving swing-out supply shafts
- Drop-in Quick Grip rewind shafts
- Photoelectric eye for operator safety
- Independent top and bottom heaters
- Web clutch adjustment for consistent output quality
- Includes rear rewind with inline rotary slitters (roll-to-roll). Note: Slitters not for use with thermal films.
- Swing-up feed table and 38" input height
- **Two year warranty includes parts and labor!**





Scan the QR code to watch demo videos for the GFP 865DH-4RS.

- Product walk-throughs: installation, features, internal views
- Applications: roll-to-roll, mounting, pre-coating, cut-sheet, and more

Rugged Design • Professional Quality • Proven Performance • Economically Priced

Item	Specification
Laminating Width	63"
Roller Diameter	5"
Maximum Speed (ft/min)	13 ft/min
Main Roller	Silicone
Maximum Roller Gap	1"
Roller Gap Adjustment	Dual Hand Crank
Unwinds	Top/bottom
Liner Rewind	Chain Drive
Supply Shafts	3 (Two Swing-Out 3" Quick Grip)
Tension Adjustment	Single Knob
Maximum Supply Roll Diameter	8" Top/16" Bottom
Swing-Out Shaft Maximum Weight	115 lbs.
Maximum Temperature	266°F
Heating Element	Quartz Heater
Roller Heating	Top & Bottom
Thermal Film Thickness	1.5 - 10mil
Power Requirements	240V Single Phase 24A
Power Consumption	5760W
Rear Rewind With Slitters	Included
Foot Pedal	Included
Stand With Casters	Included
Machine Dimensions (L x W x H)	87"x 34"x 49"
Net Weight With Stand	846 lbs



cTUVus
Safety Approval

Your Local Dealer:



gfpartnersllc.com | 800.986.2005