

Gfp Mounting Adhesive Products

Flawless finish. Flexible applications. Superior Bond.

Designed for professional digital print mounting applications, Gfp mounting adhesives deliver reliable, long-lasting performance across a wide range of substrates. All products feature 1 mil pressure-sensitive permanent adhesive with neutral 7.0 pH for long-term image stability.

Clear Mount

- 1 mil (25 μ) clear polyester mounting adhesive.
- Clear polyester carrier coated on both sides with permanent solvent acrylic adhesive. One side bonds to the printed image and the other to the mounting board.
- Provides reliable adhesion to paper-faced boards such as Gatorfoam[®] and low-energy plastics including polystyrene, Sintra[®], Gatorboard, and Ultraboard[™].

Recommended for: Decaling printed images or pre-coating mounting boards prior to mounting.

White Mount

- 3 mil (75 μ) white polypropylene mounting adhesive.
- White polypropylene carrier with 87% opacity designed to reduce color shift when mounting graphics to dark substrates such as Black Gatorboard.
- Coated on both sides with aggressive water-based acrylic adhesive for strong, consistent bonds.

Recommended for: Decaling printed images or mounting to dark boards where bleed-through must be prevented.

Front Mount

- 1.4 mil (36 μ) optically clear polyester mounting adhesive.
- Optically clear polyester carrier coated on both sides with permanent solvent acrylic adhesive for face mounting graphics to clear substrates.
- The printed image is viewed through materials such as Plexiglas[®], acrylic, polycarbonate, or glass, creating a premium display finish.

Recommended for: POP displays, window graphics, backlit displays, trade show graphics, and promotional signage.



Mounting Adhesive Technical Specs

Clear Mounting Adhesive (MAC)	
Base Carrier	0.9 mil (23 μ) Clear Polyester (PET)
Adhesive #1	1.0 mil (25 μ) Permanent Clear Solvent-based Acrylic
Adhesive #2	1.0 mil (25 μ) Permanent Clear Solvent-based Acrylic
Liner	75# (110gsm) two side PE coated and siliconized white Kraft paper
pH-value	Approximately 7.0 neutral
Durability	Up to 2 years, vertical exposure outdoors

White Mounting Adhesive (WMA)	
Base Carrier	3.0 mil (75 μ) White Biaxially oriented Polypropylene
Adhesive #1	1.0 mil (25 μ) Permanent Clear Water-based Acrylic
Adhesive #2	1.0 mil (25 μ) Permanent Clear Water-based Acrylic
Liner	60# (88gsm) two side PE coated and siliconized white Kraft paper
pH-value	Approximately 7.0 neutral
Opacity	87%
Durability	Up to 2 years, vertical exposure outdoors

Front Mounting Adhesive (MAF)	
Base Carrier	1.4 mil (36 μ) Optically Clear Polyester (PET)
Adhesive #1	1.0 mil (25 μ) Permanent Clear Solvent-based Acrylic
Adhesive #2	1.0 mil (25 μ) Permanent Clear Solvent-based Acrylic
Liner #1	1.4 mil (36 μ) Siliconized Clear Polyester (PET)
Liner #2	1.4 mil (36 μ) Siliconized Clear Polyester (PET)
pH-value	Approximately 7.0 neutral
Durability	Up to 2 years, vertical exposure outdoors

Mounting Adhesive Roll Rolls Sizes & Part Numbers

Clear Mount	
Part Number	Roll Size
MAC-5130	51" x 30'
MAC-25150	25" x 150'
MAC-38150	38" x 150'
MAC-43150	43" x 150'
MAC-51150	51" x 150'
MAC-54150	54" x 150'

Clear Mount	
Part Number	Roll Size
WMA-5130	51" x 30'
WMA-38150	38" x 150'
WMA-51150	51" x 150'
WMA-61150	61" x 150'

Clear Mount	
Part Number	Roll Size
MAF-5130	51" x 30'
MAF-38150	38" x 150'
MAC-51150	51" x 150'

Application Guidelines

Gfp Mounting Adhesives are suitable for short- to medium-term indoor or outdoor signage applications for up to 2 years with vertical exposure under normal conditions, and application temperatures ranging from 40°F to 176°F.

Bond strength depends on the amount of adhesive contact developed with the mounting surface. Applying firm pressure and moderate heat will help the adhesive achieve optimal contact.

For best results, mounting surfaces must be clean and dry. Surface preparation may be required prior to mounting, including wiping with alcohol, light sanding, or surface sealing depending on the substrate.

Important Notice

Gfp products are warranted to be free from defects in material and workmanship (see Gfp Product Warranty Statement). Product information is based on research the company believes to be reliable; however, such information is provided without guarantee and does not constitute a warranty.

Users should conduct their own evaluation of the product prior to use to determine its suitability for their specific application. The purchaser assumes all risks associated with product use.

Your Local Dealer:

