

Gfp 563TH-4RS

Production Top-Heat Laminator

Take your production to the next level.
Load faster. Change less. Finish more.

With swing-out shafts and quick application changes, the 563TH-4RS helps you move from job to job with up to 50% faster throughput – saving you time, effort, and money.



Includes motorized rear rewind with rotary slitters for roll-to-roll applications.



Swing-Out Shafts for fast roll changes



Perfect for mounting, overlamination, and board pre-coating.

Built for Performance

- Inline Rotary Slitters for maximum productivity
- Media alignment disks keep supply rolls from telescoping
- 3" Quick Grip Shafts for easy loading
- Metal Alloy Heaters for durability
- Roll-to-Roll Operation for versatility

Ideal Applications:


- Signs and Banners
- POP Displays
- Trade Show Graphics
- Photo and Graphic Mounting
- Dry-Erase Boards
- Floor and Window Graphics

- Vehicle Graphics

Key Features

- Swing-Out Quick Grip Supply Shafts
- Drop-In Quick Grip Rewind Shafts
- Photoelectric Eye for safety
- Rear Rewind with Rotary Slitters (included)
- Swing-Up Feed Table with 38" input height
- Metal Alloy Heater for greater durability
- 4.5" Diameter Rollers
- Roller Gap Measurement Scale
- Installation available
- **Two year warranty includes parts and labor!**





Scan the QR code to watch demo videos for the GFP 563TH-4RS.

- Product walk-throughs: installation, features, internal views
- Applications: roll-to-roll, mounting, pre-coating, cut-sheet, and more

Rugged Design • Professional Quality • Proven Performance • Economically Priced

Item	Specification
Laminating Width	63"
Roller Diameter	4.5"
Maximum Speed (ft/min)	20 ft/min
Main Roller	Silicone
Maximum Roller Gap	1"
Roller Gap Adjustment	Hand Wheel
Unwinds	Top/bottom
Liner Rewind	Chain Drive
Supply Shafts	Two Swing-Out 3" Quick Grip
Tension Adjustment	Single Knob
Maximum Supply Roll Diameter	8" Top/16" Bottom
Swing-Out Shaft Maximum Weight	115 lbs.
Maximum Temperature	140°F
Heating Element	Metal Alloy Heater
Power Requirements	110V 12A
Power Consumption	1320W
Rear Rewind With Slitters	Included
Foot Pedal	Included
Stand With Casters	Included
Machine Dimensions (L x W x H)	87"x 26.5"x 52.5"
Net Weight With Stand	491 lbs.
Shipping Dimensions (L x W x H)	90"x 33"x 46" (828 lbs)



cTUVus
Safety Approval

Your Local Dealer:



gfpartersllc.com | 800.986.2005