

Gfp Machine Overview

WIDE FORMAT LAMINATORS
RUGGED DESIGN
PROFESSIONAL QUALITY
PROVEN PERFORMANCE
ECONOMICALLY PRICED



	865DH-4RS	663TH	563TH-4RS	363-TH	355-TH
Heat / Cold	Dual Heat	Top Heat Assist	Top Heat Assist	Top Heat Assist	
Laminating Width	65"	63"	63"	63"	55"
Maximum Speed (feet/minute)	13	20	20	20	
Speed Control	Variable	Variable	Variable	Variable	
Maximum Temperature	266° F	140°F	140°F	140°F	
Heating Method	Quartz Tube	Metal Alloy	Metal Alloy	Metal Alloy	
Mounting Gap	1"	1"	1"	1"	
Pressure/Gap Adjustment	Infinite	Infinite	Infinite	Infinite	
Pressure/Gap Mechanism	Dual Hand Wheel	Electric	Hand Wheel	Hand Wheel	
Roller Diameter	5"	5"	4.5"	5"	
Main Rollers	Silicone	Silicone	Silicone	Rubber	
Supply Shaft	Swing Out with 3" Quick Grip	Swing Out with 3" Quick Grip	Swing Out with 3" Quick Grip	3" Quick Grip	
Tension Adjustment	Single Knob	Single Knob	Single Knob	Single Knob	
Film Tension Sensor	-	✓	-	-	
Digital Microcontroller	-	✓	-	-	
Color Graphic Display	-	✓	-	-	
Touchscreen Interface	-	✓	-	-	
Operating Tutorials	-	✓	-	-	
Roll Label Printer	-	✓	-	-	
Web Clutch	✓	-	-	-	
Motorized Liner Rewind	✓	✓	✓	Chain Link	
Roll to Roll Capable	✓	✓	✓	✓	
Rear Rewind	✓	✓	✓	✓	
Inline Slitting	✓	✓	✓	-	
Front Unwind	2	✓	✓	✓	
Foot Pedal	✓	✓	✓	✓	
Optical Safety Eyes	✓	✓	✓	✓	
Stand	✓	✓	✓	✓	
Swing Up Feed Table	✓	✓	✓	✓	
Power Supply	240v 24A	120v 12A	110v 12A	120v 12a	120v 11a
Power Consumption	5760W	1440W	1320W	1440W	1320W
Warranty Parts	2 years	2 years	2 years	2 years	2 years
Warranty Labor	2 years	2 years	2 years	2 years	2 years
Installation & Training	Included	Optional	Optional	Optional	
Net Weight (LBS.)	846	675	491	376	321
Dimensions	87" x 34" x 49"	83" x 31" x 63"	87" x 26.5" x 52.5"	80" x 23" x 48"	72" x 23" x 48"
Safety Approval	cTUVus	cTUVus	cTUVus	cTUVus	cTUVus

Gfp Machine Overview

WIDE FORMAT LAMINATORS
RUGGED DESIGN
PROFESSIONAL QUALITY
PROVEN PERFORMANCE
ECONOMICALLY PRICED



	263-C	255-C	230-C	220-C
Heat / Cold	Cold		Cold	Cold
Laminating Width	63"	55"	30"	20"
Maximum Speed (feet/minute)	13		11.5	11.5
Speed Control	Variable		Variable	Variable
Maximum Temperature	-		-	-
Heating Method	-		-	-
Mounting Gap	1"		1/2"	1/2"
Pressure/Gap Adjustment	Infinite		Infinite	Infinite
Pressure/Gap Mechanism	Hand Wheel		Hand Wheel	Hand Wheel
Roller Diameter	4.5"		2.5"	2.5"
Main Rollers	Rubber		Rubber	Rubber
Supply Shaft	3" Quick Grip		3" Quick Grip	3" Quick Grip
Tension Adjustment	Single Knob		Single Knob	Single Knob
Film Tension Sensor	-		-	-
Digital Microcontroller	-		-	-
Color Graphic Display	-		-	-
Touchscreen Interface	-		-	-
Operating Tutorials	-		-	-
Roll Label Printer	-		-	-
Web Clutch	-		-	-
Motorized Liner Rewind	Chain Link		✓	✓
Roll to Roll Capable	-		-	-
Rear Rewind	-		-	-
Inline Slitting	-		-	-
Front Unwind	✓		✓	✓
Foot Pedal	✓		✓	✓
Optical Safety Eyes	✓		✓	✓
Stand	✓		✓	Optional
Swing Up Feed Table	Fixed		✓	✓
Power Supply	110v 0.4A		110v 0.4A	110v 0.3A
Power Consumption	44W		33W	33W
Warranty Parts	2 years	2 years	2 years	2 years
Warranty Labor	2 years	2 years	2 years	2 years
Installation & Training	Optional		Optional	Optional
Net Weight (LBS.)	322	257	120	113
Dimensions	80" x 24" x 55"	73" x 24" x 55"	43" x 17" x 42"	16" x 22" x 38" w/o stand
Safety Approval	cTUVus	cTUVus	cTUVus	cTUVus